

MARSH®

Safety Valve

Description

Safety Relief Valves are available in 1/8, 1/4 and 3/8 BSP, and with Ring Pull Test or Tamper Proof cap, and are CE Marked and certified.

Also available, on request - 1/2 and 1" BSP.

Many Factory Set SR Valves are held in stock at our Head Office in Nottingham, and are very economically priced.

Specifications

Seal	NBR
Body	Brass
Spring	Steel C98
Tamper proof cap	Available
Manual ring pull test	Standard
Certification	CE PED Cat. IV

Please contact 0115 9933300 for more details and technical



Typical Discharge Rates

1/4 BSP Model - Lt/Min - Real Discharge

BAR	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Lt / min	123	185	333	507	875	1234	1602	2350	2690	3040	3464	3665	3741	3873	4000	4604

3/8 BSP Model - Lt/Min - Real Discharge

BAR	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Lt / min	311	519	866	1229	1918	2645	3441	4200	4980	5804	6856	7812	9342	9682	10000	11056

1/2 BSP Model - Lt/Min - Real Discharge

BAR	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
Lt / min	531	1062	1593	2125	2655	3186	3717	4250	5955	8015	8949	10095	10601	11295	12050	12804	13604	14419

1 BSP Model - Lt/Min - Real Discharge

BAR	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
Lt / min	2120	3220	4320	5072	6172	7272	7944	8616	9288	9948	10584	11208	11820	12408	12996	13584	14172	14760

Repairs and Calibration

From our Works at Nottingham we are also able to offer repair and Certified recalibration of all our Safety Relief Valves, at realistic prices.

We can also undertake recalibration of other makes of Safety relief Valves.

MARSH BELLOFRAM®
Group of Companies

9 Castle Park Queens Drive, Nottingham NG2 1AH England

Tel: (44) 115 993 3300 • Fax: (44) 115 993 3301 • e-mail: bellofram@aol.com • www.marshbellofram.com

LTUK09030